


# TECHNICAL CHARACTERISTICS

OENOLOGICAL TANKS STANDING ON LEGS

WITH SPIRAL RUNNER COOLING JACKET

LEGEND – CLASS ACCESSORIES

5	Air valve with double effect PVC until 250 hl, beyond stainless steel
7	Central top manhole Ø400 H structure =60 mm
8	Supporting legs AISI 304
9	Level indicator outlet
10	Level indicator outlet pipe
11	Level indicator inlet
12	Level indicator
13	Ball valve for partial draining AISI 304
17	Ball valve for full draining AISI 304
18	Raising lugs
27	Manufacturer plate
28	Elliptical manhole Ø440x305 mm hence 20 hl
29	Sample groups hence 15hl
30	Digital thermometer
43	Spiral runner thermal exchange surface
62	Drill holder



(\*) Butterfly Finishing: 2B

CAPACITY		Diameter Tank	HEIGHT					THICKNESS (*)			Valve Ø	Spiral Runner S
Nom.	Real		Cylinder HC	Top T	Bottom F	Legs G	TOT Ht	Ferrules	Top	Bottom		
hl	hl	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
14	14,9	1194	1250	120	120	470	2050	2,0	1,5	1,5	40	785
20	20,5	1194	1750	120	120	470	2550	2,0	1,5	1,5	40	1065
25	25,1	1194	2160	120	120	470	2960	2,0	1,5	1,5	40	1065
30	30,5	1433	1800	140	140	600	2750	2,0	1,5	1,5	40	1065
40	41,9	1592	2000	160	160	600	2970	2,0	1,5	1,5	40	1065
50	51,9	1592	2500	160	160	600	3470	2,0	1,5	2,0	40	1065
60	62,0	1592	3000	160	160	600	3970	2,0	1,5	2,0	50	1065
80	84,0	1990	2500	300	300	600	3610	2,0	1,5	2,0	50	1065
100	100,0	1990	3000	300	350	600	4110	2,0	1,5	2,0	50	1065
120	122,4	2200	3000	220	440	750	4180	2,0	1,5	2,5	50	1065
150	156,3	2388	3250	240	480	750	4450	2,0-1,5	1,5	2,5	60	1065
200	208,8	2500	4000	260	500	850	5320	2,0-1,5	2,0	3,0	60	1065
250	257,9	2500	5000	260	500	850	6320	2,0-1,5	2,0	3,0	60	1205
300	307,0	2500	6000	260	500	850	7320	2,0-1,5	2,0	3,0	60	1205
350	356,4	2500	7000	260	500	850	8320	2,5-2,0-1,5	2,0	3,0	80	785+785
400	410,0	3000	5500	300	600	850	6860	2,5-2,0-1,5	2,0	4,0	80	1205
450	463,0	3000	6250	300	600	850	7610	2,5-2,0-1,5	2,0	4,0	80	1205
500	516,0	3000	7000	300	600	850	8360	3,0-2,5-2,0-1,5	2,0	4,0	80	785+785
600	604,4	3000	8250	300	600	850	9610	3,0-2,5-2,0-1,5	2,0	4,0	80	785+785